

VELUX roof window GVO

Glazing 59H SILAN

VELUX®



The window can be installed in roof pitches between 20° and 60°.



Our classical roof window GVO with curved top is a modern alternative to a traditional cast iron roof window. Made from maintenance-free polyurethane and aluminium. Comes complete with integrated flashing for easy installation and integrated roller blind for heat protection. VELUX classical roof window GVO is the aesthetic solution for historical buildings.

- All the benefits of a modern roof window in a traditional conservation design.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the extruded aluminium sash.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.
- Top-hung window with harmonic and symmetric aesthetics when opened.
- Built-in roller blind provides basic heat protection and privacy.

Available sizes and daylight area

	540
760	GVO (0.37)

All measurements are in mm. () = Effective daylight area, m²

Glazing features

Glazing 59H SILAN		
	Heat insulation The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.	U_g = 1.4
	Solar gain In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.	g = 0.64
	Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.	★★☆☆
	Sound insulation A combination of laminated glass and extra thick glass provides better sound insulation against noise from outside (traffic, playgrounds, etc).	R_w dB = 24(0;-2)
	Security Thicker laminated inner glass increases resistance to manual attack (burglary).	N/A
	Toughened glass Adds strength to the outer pane to protect from wayward balls and extreme weather such as heavy storms and hail.	✓

Glazing structure

Glazing unit	Composition (from inside to outside)
Double-glazed	3 mm float glass - 10 mm Argon - 3 mm toughened glass

Interior finish

Material Description	Black maintenance free Finished with polyurethane lacquer.
Colour code NCS, inner surface	S 9000-N
Colour code nearest RAL, inner surface	9005

Exterior covers

Material Description	Aluminium, dark grey Dark grey
Colour code NCS, outer surface	S 7500-N
Colour code nearest RAL, outer surface	7043

Guarantee period

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.