

VELUX craftsman's roof exit GVK



Glazing 00H



The window can be installed in roof pitches between 20° and 65°.



VELUX roof window GVK is designed for use in uninhabited rooms where easy access to the roof and regular ventilation is needed. Side-hung, it opens to the left or right depending on preferred use. Made from maintenance-free aluminium and polyurethane. Comes complete with integrated flashing and moulded tread. Available with black profiles.







- Three ventilation positions enable you to secure a constant low-level air flow in uninhabited areas.
- Opens outwards to the left or the right for easy access to the roof.
- Patented opening restrictor securely holds the window open at 90-degrees.
- Maintain the traditional exterior expression of the building with the traditional design.
- Enjoy hassle- and maintenance-free use of the roof window thanks to the extruded aluminium sash.
- Create a perfect installation with the integrated universal flashing that provides a simple workflow and a watertight connection.

Available sizes and daylight area

	460
610	GVK (0.22)

All measurements are in mm. () = Effective daylight area, m²

Glazing features

Glazing 00H		
	Heat insulation The low energy glazing unit reduces heat loss through the window and enhanced indoor comfort.	U_g = 3.0
	Solar gain In colder climates and in rooms with large window areas, solar gain provides a better indoor climate during winter periods.	g = 0.78
	Solar protection In warm climates and in rooms with large window areas, a sun protective glazing unit provides a better indoor climate during summer periods.	★★☆☆
	Sound insulation A combination of laminated glass and extra thick glass provides better sound insulation against noise from outside (traffic, playgrounds, etc).	R_wdB = npd
	Security Thicker laminated inner glass increases resistance to manual attack (burglary).	N/A

Glazing structure

Glazing unit	Composition (from inside to outside)
Double-glazed	3 mm inner float glass - 10 mm air - 3 mm outer float glass

Interior finish

Material Description	Black maintenance free Finished with polyurethane lacquer.
Colour code NCS, inner surface	S 9000-N
Colour code nearest RAL, inner surface	9005

Exterior covers

Material Description	Aluminium, dark grey Dark grey
Colour code NCS, outer surface	S 7500-N
Colour code nearest RAL, outer surface	7043

Guarantee period

Further information

We reserve the right to make technical changes.

For more information on our products, please visit <https://velux.com>.